

---

# Django Perseus Documentation

*Release 0.1*

**Carlo Smouter**

February 05, 2015



<b>1</b>	<b>Why would I need this?</b>	<b>3</b>
<b>2</b>	<b>Downsides</b>	<b>5</b>
<b>3</b>	<b>Credits</b>	<b>7</b>
<b>4</b>	<b>Contents</b>	<b>9</b>
4.1	Installation . . . . .	9
4.2	Usage . . . . .	9
<b>5</b>	<b>Indices and tables</b>	<b>13</b>



Builds a static version of your Django website.



---

## Why would I need this?

---

Let's say your webhost can only serve static files, then this package can statically generate your Django website and you can upload the result to your webhost.



---

## Downsides

---

On a static website some restrictions apply:

- No conditions in template. `{% if %}` `{% else %}` blocks will not be very effective.
- No user input. No forms or dynamic pages.



---

### Credits

---

This project is based on the Django Medusa app which allows to render a Django website statically Thanks Mike Tigas for your work :)

- [Django Medusa on Github](#)



## 4.1 Installation

- Install Django Perseus:

```
pip install django-perseus
```

- Add 'django\_perseus' to your INSTALLED\_APPS setting:

```
INSTALLED_APPS = (  
    # ...  
    "django_perseus",  
)
```

## 4.2 Usage

Django Perseus consists of few modules working together to successfully render a static html site.

- **Template tags** They overwrite Django's builtin url and static tags to rewrite them statically.
- **Renderer** Selects views and renders them as static pages.
- **Importer** Imports a selection of static and media files to the output directory of the renderer.

### 4.2.1 Renderer

Django Perseus will look for renderers.py file in your Django apps.

You can subclass the `BaseRenderer` to create a custom renderer, or use the `DefaultRenderer` to render your Django website with the default behaviour.

```
from django_perseus.renderers.default import DefaultRenderer
```

```
class AppRenderer(DefaultRenderer):
```

```
    def paths(self):  
        return [  
            reverse('index'),  
            reverse('privacy'),  
            reverse('app:index'),
```

```
reverse('app:settings'),
reverse('app:detail', kwargs={'pk': 1}),
reverse('app:archive', kwargs={'year': 2014, 'week': 52}),
]
```

```
renderers = [AppRenderer, ]
```

The output of the example will be:

```
output_dir/index.html
output_dir/privacy.html
output_dir/app.html
output_dir/app/settings.html
output_dir/app/detail/1.html
output_dir/app/archive/2014/52.html
```

### 4.2.2 Importer

You can subclass `BaseImporter` to import files from specific locations in your Django app to a target directory

Your static website will need a selection of media and static files.

The `BaseImporter` accepts the following class attributes:

- `target_dir` (Django setting) the target directory where the files will be copied to.
- `source_dir` (Django setting) the source directory where the files will be copied from.
- `sub_dirs` (List) subdirectories or files to be imported.

Example media files importer:

```
class MediaImporter(BaseImporter):

    target_dir = 'PERSEUS_SOURCE_DIR'
    source_dir = 'MEDIA_ROOT'
    sub_dirs = [
        '*'
    ]
```

Example static files importer:

```
class StaticImporter(BaseImporter):

    target_dir = 'PERSEUS_SOURCE_DIR'
    source_dir = 'STATIC_ROOT'
    sub_dirs = [
        'css',
        'img',
        'js/build',
        'robots.txt',
    ]
```

Register the importer subclass in your perseus settings file:

```
PERSEUS_IMPORTERS = [
    'yourproject.app.importers.MediaImporter',
    'yourproject.app.importers.StaticImporter',
]
```

### 4.2.3 Template tags

The tags rewrite paths when the `render` management command is run with a settings file containing the setting:  
`RENDER_STATIC = True`

Load the tags in your templates as:

```
{% load django_perseus_tags %}
```

### 4.2.4 Management command

The `render` management command will run all renderers found in your Django apps and run the file importers.

```
./manage.py render --settings=yourproject.conf.perseus_settings.py
```

To also output the result in a zip archive, run as:

```
./manage.py render --archive --settings=yourproject.conf.perseus_settings.py
```

```
./manage.py render --archive --filename filename.zip --settings=yourproject.conf.perseus_settings.py
```

### 4.2.5 Settings

- **RENDER\_STATIC** A boolean whether the url and static tags will be rewritten to static paths.
- **PERSEUS\_SOURCE\_DIR** renderer output folder
- **PERSEUS\_BUILD\_DIR** output dir if render management command runs with `--archive` option
- **PERSEUS\_IMPORTERS** A list where Importers are to be found.

```
PERSEUS_IMPORTERS = [  
    'yourproject.app.importers.MediaImporter',  
    'yourproject.app.importers.StaticImporter',  
]
```



---

## Indices and tables

---

- *genindex*
- *modindex*
- *search*